

ERC



PT-5700

the New Partner Tech point of sale solution All-In-One, Touchscreen POS Terminal

- **Fanless**
- **Reliable, retail-hardened construction**
- **Open operating system architecture**
- **Compact footprint design**
- **Low cost of ownership**
- **Thin-client or Thick-client platform**
- **Fully integrated, plug and play system**
- **Integrated biometric reader, touch display, magnetic strip reader (MSR) and keyboard**



Biometric



Rear Display



Keypad



MSR

ERC PT-5700

Wall Mount



The Partner Tech 5700 delivers the answer to today's demanding questions:

Fanless, Power, Speed, Reliability and Low Total Cost of Ownership. The eye pleasing physical appearance of the PT-5700 can be configured with a variety of industry standard peripherals offered by Partner Tech to meet the demands of food-service, specialty retail, and virtually any hospitality environment.

- Proven 2nd generation fanless design
- Small footprint
- Integrated biometrics scanner, card reader and keypad
- Enhanced touch screen technology, capacitive or resistive touch versions
- Ultra fast integrated 10/100/1G network interface
- Open Operating System architecture for the latest POS software
- Multiple accessory design options to fit your needs



This sleek yet economical POS system is built to work in the typical harsh retail, hospitality and food service environments. It is engineered for easy set-up, quick serviceability and rigorous use that are characteristic of most POS settings. With simple access to connectivity for peripherals and a built-in open architecture to load any software application, the PT-5700 helps lower your total cost of ownership and increase sales efficiency.

Specifications

| | |
|--------------------------|---|
| Processor | VIA Eden (V4 Bus) 1GHz CPU@400MHzFSB |
| System Memory | 512MB DDR2 SO-DIMM memory up to 1Gb, 1 slot |
| Display | 15 Active TFT color LCD |
| Resolution | 1024x768 (Optional: 800x600) |
| Brightness | 250 nit |
| Viewing Angle | 0° to 60° tilt |
| Touch Screen | ELO 5-wire resistive or optional capacitive |
| Network | Ethernet 10/100/1G |
| Storage | 3.5" 80G hard drive |
| Expansion Options | Compact flash card socket • IDE interface • 1 mini-PCI |
| Power Supply | 100-240vAC, DC +19V, 90W power adaptor |
| I/O Ports | • 4 p-sub 9 RS232 ports provide +5V/12V through jumper Iree BIOS setting. • 1 parallel port • 1 PS/2 KB • 1 PS/2 mouse • 2 USB 2.0 ports in front, 2 USB 2.0 ports in rear • 1 DB-15 VGA port • 1 RS45LAN port • 1 RJ-11, 24Vdc cash drawer port supports two cash drawers • 2 Audio ports(1line-out, 1 MIG-in) |
| Operating System | Windows 98 /2000 /XP Pro /XPE /CE.Net /WEPOS /Linux |
| Peripherals | • Dual or three track magnetic card reader • Biometric Reader, Smart Card Reader, • KB-32 32 key keypad • 2x20VFD customer display |
| Temperature | • Operating Temperature: 0-40°C • Storage Temperature: -20-60°C |
| Humidity | • Operating Humidity: -20%-85% • Storage Humidity: -5%-85% |
| Dimension | • Physical: 10.9x8.5x14.1 inch • Package: 16.1x18.5x15.8 inch |
| Weight | 20.9 lbs |
| Certification | CE/FCC Class A, UL, cUL, VCCI, BSMI, ROHS |

Contact your ERC representative today for your choice in POS and Wireless System solutions!



4001 Cobb International Blvd., Kennesaw, GA 30152
800.241.6880, www.eronline.com